



## SPECIFICATIONS – AVANT 528

LIFT CAPACITY

**950  
kg**

ENGINE POWER

**26 hp  
diesel**

LIFT HEIGHT

**2.8 m**

SPEED

**12  
km/h**



# AVANT<sup>®</sup>

(/uk)  
UK

## SPECIFICATIONS

<b>LENGTH</b>	2570 mm
<b>WIDTH</b>	1130 mm
<b>HEIGHT</b>	1985 mm
<b>WEIGHT</b>	1250 + 170 kg
<b>STANDARD WHEELS</b>	23x10.50-12"grass/TR
<b>TRANSMISSION, DRIVE</b>	hydrostatic Avant Optidrive™
<b>PULLING FORCE</b>	950 kp
<b>DRIVE SPEED MAX.</b>	12 km/h
<b>AUX. HYDRAULICS OIL FLOW / PRESSURE</b>	36 l/min 200 bar
<b>HYDRAULIC OIL COOLER</b>	standard
<b>TURNING RADIUS INSIDE/OUTSIDE</b>	995 / 2050 mm
<b>MAX. LIFTING HEIGHT</b>	2790 mm
<b>TIPPING LOAD</b>	950 kg
<b>MAX. BREAKOUT FORCE / 50 CM</b>	1250 kg
<b>ENGINE MAKE AND TYPE</b>	Kubota D1105 Stage V
<b>ENGINE OUTPUT (ISO GROSS)</b>	19 kW (26 hp)
<b>MAXIMUM TORQUE</b>	72 Nm @ 2200 rpm
<b>FUEL</b>	Diesel
<b>PRODUCT NO.</b>	A424277



## WIDTH

WHEEL SIZE	PROFILE	MACHINE WIDTH
27 x 8.50 - 15 *)	tractor	1030 mm
23 x 8.50 - 12	tractor or grass	1080 mm
23 x 10.50 - 12	tractor or grass	1130 mm
26 x 12.00 - 12 *)	tractor or grass	1290 mm
320/60 - 12 HD *)	tractor	1290 mm
26,5 x 14.00 - 12 **)	grass	1420 mm

\*) Bigger wheels will increase total machine height by 20-35 mm

\*\*) requires 40 mm spacers on the wheel hubs

\*\*\*) Road traffic light kit width for ROPS safety frame is 1090 mm

## HEIGHT WITH CAB

WHEEL SIZE	26X12.00-12 OR 320/60-12*	27X8.50-15
L Cab	2035 mm	2048 mm
LX Cab	2025 mm	2038 mm
DLX Cab	2045 mm	2058 mm

\*) With 23" wheels machine is 15 mm lower



**AVANT**<sup>®</sup>  
(/uk)  
UK

# DIMENSIONS



**ask a question.**