

Mini Track Loaders / MT100 Mini Track Loader

MT100 Loader Specifications & Options

Review complete specs for the MT100 mini track loader and see how it stacks up to other models.

Standard

☒

 Optional

N/A

 Not Applicable

Units

METRIC

Bobcat MT100	
Engine	
Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Displacement	900 cm³
Number of Cylinders	3
Horsepower	18.49 kW (25.14 hp)
Performance	
Rated Operating Capacity (ISO)	454 kg
ROC (ISO) with Standard Counterweight - Undercarriage Position	n/a
ROC (ISO) with Standard Counterweight - Rear Upright Position	n/a
Carry Position ROC with Standard Counterweight - UnderCarriage Position	n/a
Carry Position ROC with Standard Counterweight - Rear Upright Position	n/a
Tipping Load	1315 kg
Operating Weight	1538 kg
Ground Pressure (Rubber)	0.36 bar
Travel Speed	6.6 km/h
Travel Speed - Reverse	4.7 km/h

Capacities

Fuel Tank	26.5 l
-----------	--------

Hydraulic System

Pump Capacity	45.4 l/min
System Relief @ Quick Couplers	199.95 bar
Auxiliary Std Flow	45.42 l/min

Dimension

Length	2697 mm
Width	904 mm
Height	1387 mm
Height to Bucket Hinge Pin	2055 mm
Length of track on ground	1052 mm
Reach @ Maximum Height	472 mm

Features

Lift-Arm Support	■
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Reverse Travel Stop Panel	N/A
Wide Track	☑
Neutral Start Interlocks	■
Lift Arm Lockout With Manual Bypass	■
Tilt Lockout	■
Built-In Tie Down & Crane/Lift Locations	■
Ride-on Platform	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.